

SAFETY DATA SHEET

COLOROBE	BIA I	ITALIA	HTL000001					
S.P.A.								
Date of printing	:	17.07.2023	Date of issue	:	13.06.2023	Issue/Revision	:	4.0

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name HTL--000001

Product code 000000000010057847

Product description Not available.

liquid **Product type**

Other means of identification HTL--000001-H002

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Third firing decoration in the glass/ceramics/porcelain sectorsThird

firing decoration in the glass/ceramics/porcelain sectors

1.3 Details of the supplier of the safety data sheet

COLOROBBIA ITALIA S.P.A. Indirizzo via Pietramarina 53

Località e Stato 50053 Sovigliana - Vinci (FI)

Italia

tel. +39 0571 7091 fax +39 0571 709.850

e-mail address of person responsible for this SDS

1.4 Emergency telephone number

QHSE@colorobbia.it

National advisory body/Poison Center

Telephone number CAV - Ospedale Pediatrico Bambino Gesù - Roma - tel. +39 06

Az. Ospedaliera Università Foggia - Foggia - tel. 800183459 Az. Ospedaliera - A. Cardarelli- Napoli- tel. +39 081 7472870 CAV - Policlinico Umberto I- Roma - tel. +39 06 49978000 CAV - Policlinico A. Gemelli - Roma - tel. +39 06 3054343

Az. Ospedaliera Careggi - U.O. Tossicologia Medica - Firenze - tel.

+39 055 7947819

CAV - Centro Nazionale di Informazione Tossicologica - Pavia - tel.

+39 0382 24444

Ospedale Niguarda Ca' Granda - Milano - tel. +39 02 66101029 Az. ospedaliera Papa Giovanni XXIII - Bergamo - tel. 800883300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 Repr. 1B, H360

STOT SE 3, H335 (Respiratory tract irritation)

STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms









Signal word Hazard statements Danger

: H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated

exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

General: P103 - Read carefully and follow all instructions.P102 - Keep out of

reach of children.P101 - If medical advice is needed, have product

container or label at hand.

Prevention : P201 - Obtain special instructions before use. P280 - Wear protective

gloves, protective clothing, eye protection, face protection, or hearing protection. P284 - Wear respiratory protection. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P260 - Do not breathe vapor. P270 - Do not eat, drink

or smoke when using this product. P264 - Wash thoroughly after

handling.

Response P391 - Collect spillage. P308 - IF exposed or concerned: P308 +

P313 - Get medical advice or attention. P304 - IF INHALED: P304 +

P340 - Remove person to fresh air and keep comfortable for

breathing. P304 + P312 - Call a POISON CENTER or doctor if you feel unwell. P342 - If experiencing respiratory symptoms: P342 + P311 - Call a POISON CENTER or doctor. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 - IF ON SKIN: P302 + P352 - Wash with plenty of water. P333 - If skin irritation or rash occurs: P333 + P313 - Get medical advice or attention. P305 - IF IN EYES: P305 + P351 + P338 - Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. P305 + P310 - Immediately call a POISON

CENTER or doctor.

P405 - Store locked up.P403 + P233 - Store in a well-ventilated **Storage**

place. Keep container tightly closed.

Disposal P501 - Dispose of contents and container in accordance with all

local, regional, national and international regulations.

cyclohexanol **Hazardous ingredients**

bornan-2-one

rosin

formaldehyde, reaction products with butylphenol

turpentine, oil dodecane-1-thiol linalool

4-methylpentan-2-one

eugenol cineole

(R)-p-mentha-1,8-diene

pin-2(3)-ene (E)-anethole pin-2(10)-ene

Not applicable. **Supplemental label elements**

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Yes, applicable.

Tactile warning of danger Yes, applicable.

2.3 Other hazards

for PBT or vPvB

Product meets the criteria: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

according to Regulation (EC) No. 1907/2006,

Annex XIII

Other hazards which do : None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
cyclohexanol	EC: 203-630-6 CAS: 108-93-0 Index: 603-009-00-3	>= 10 - <= 25	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 STOT SE 3, H335 (Respiratory tract irritation)	ATE [Oral] = 1.400 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1]
bornan-2-one	EC : 200-945-0 CAS : 76-22-2	>= 10 - <= 25	Flam. Sol. 2, H228 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 4, H413	-	[1]
rosin	EC: 232-475-7 CAS: 8050-09-7 Index: 650-015-00-7	>= 10 - <= 25	Met. Corr. 1, H290 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 100 M [Chronic] = 10	[1]
formaldehyde, reaction products with butylphenol	EC: 294-145-9 CAS: 91673-30-2 Index: 605-021-00-4	> 0 - <= 10	Skin Sens. 1, H317	-	[1]
turpentine, oil	EC: 232-350-7 CAS: 8006-64-2 Index: 650-002-00-6	> 0 - <= 3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1.100 mg/kg ATE [Inhalation (vapours)] = 13,7 mg/l	[1]
Gilsonite	CAS : 12002-43-6	> 0 - <= 3	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
dodecane-1-thiol	EC: 203-984-1 CAS: 112-55-0	> 0 - <= 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 (Respiratory tract irritation)	-	[1]
linalool	EC: 201-134-4 CAS: 78-70-6 Index: 603-235-00-2	> 0 - < 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	-	[1]

4-methylpentan-2-one	EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	> 0 - < 1	Flam. Liq. 2, H225 Acute Tox. 4, H302 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 1 M [Chronic] = 1	[1] [2]
eugenol	EC : 202-589-1 CAS : 97-53-0	> 0 - < 1	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1, H317	ATE [Oral] = 1.930 mg/kg	[1]
cineole	EC: 207-431-5 CAS: 470-82-6	> 0 - < 1	Flam. Liq. 3, H226 Skin Sens. 1, H317	-	[1]
(R)-p-mentha-1,8-diene	EC: 227-813-5 CAS: 5989-27-5 Index: 601-096-00-2	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	[1]
pin-2(3)-ene	EC : 201-291-9 CAS : 80-56-8	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
camphene	EC : 201-234-8 CAS : 79-92-5	> 0 - <= 0,3	Flam. Sol. 2, H228 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
(E)-anethole	EC : 224-052-0 CAS : 4180-23-8	> 0 - <= 0,3	Skin Sens. 1, H317	-	[1]
pin-2(10)-ene	EC: 204-872-5 CAS: 127-91-3	> 0 - <= 0,3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304	-	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following: pain, watering,

Inhalation : Adverse symptoms may include the following: respiratory tract irritation, coughing, wheezing and breathing difficulties, asthma, reduced fetal weight, increase in fetal deaths, skeletal malformations

Skin contact : Adverse symptoms may include the following: pain or irritation, redness, blistering may occur, reduced fetal weight, increase in fetal

deaths, skeletal malformations

Ingestion : Adverse symptoms may include the following: stomach pains, reduced fetal weight, increase in fetal deaths, skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained

and prevented from being discharged to any waterway, sewer or

Hazardous combustion products : Do

: Decomposition products may include the following materials: carbon dioxide, carbon monoxide, sulfur oxides Decomposition products may include the following materials: carbon dioxide, carbon

monoxide, sulfur oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders

inadequate. Put on appropriate personal protective equipment.

if specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold	
E1	100 t	200 t	

7.3 Specific end use(s)

Recommendations Not available. **Industrial sector specific** Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
4-methylpentan-2-one	EU OEL (2000-06-01). TWA 83 mg/m3 20 ppm STEL 208 mg/m3 50 ppm Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (2004-03-01). TWA 83 mg/m3 20 ppm
	STEL 208 mg/m3 50 ppm

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres -Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
cyclohexanol	DNEL	Long term	1,43 mg/kg	Workers	Systemic

Date of previous issue: 18.05.2023 Version: 4.0 Date of issue/Date of revision: 13.06.2023

		Dermal	bw/day		
	DNEL	Long term	0,716 mg/kg	General	Systemic
		Dermal	bw/day	population	
	DNEL	Long term	0,716 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	40,3 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	10 mg/m ³	General	Systemic
		Inhalation		population	
bornan-2-one	DNEL	Long term	4,3478	General	Systemic
		Inhalation	mg/m³	population	
	DNEL	Long term	17,6316	Workers	Systemic
		Inhalation	mg/m³		
	DNEL	Long term	5 mg/kg	General	Systemic
		Dermal	bw/day	population	
	DNEL	Long term	5 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	10 mg/kg	Workers	Systemic
		Dermal	bw/day		
rosin	DNEL	Long term	1,0655 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Long term	10 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term	2,131 mg/kg	Workers	Systemic
		Dermal	bw/day		
turpentine, oil	DNEL	Short term	1,6 mg/kg	Workers	Systemic
		Dermal	bw/day		
	DNEL	Long term	0,11 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Short term	51,6 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Short term	10,3 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term	3,9 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term	3,17 mg/cm ²	Workers	Local
		Dermal			
	DNEL	Short term	0,59 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Short term	$0,12 \text{ mg/m}^3$	General	Systemic
		Inhalation	0.71	population	-
	DNEL	Short term	9,51 mg/cm ²	Workers	Local
		Dermal	0.50	***	a
	DNEL	Long term	$0,78 \text{ mg/m}^3$	Workers	Systemic
		Inhalation	1		<u> </u>
	DNEL	Long term	1,17 mg/kg	Workers	Systemic
		Dermal	bw/day		
	DNEL	Long term	0.018 mg/m^3	General	Systemic
		Inhalation		population	
	DNEL	Long term	0,417 mg/kg	General	Systemic
		Dermal	bw/day	population	1
linalool	DNEL	Long term	3 mg/cm ²	Workers	Local
		Dermal			
4-methylpentan-2-one	DNEL	Long term	4,2 mg/kg	General	Systemic
		Oral	bw/day	population	
	DNEL	Short term	208 mg/m ³	Workers	Systemic
		Inhalation			

	DNEL	Short term Inhalation	208 mg/m³	Workers	Local
	DNEL	Long term Inhalation	83 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	83 mg/m³	Workers	Local
	DNEL	Long term Inhalation	14,7 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	14,7 mg/m³	General population	Local
	DNEL	Long term Dermal	11,8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	155,2 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	155,2 mg/m ³	General population	Local
eugenol	DNEL	Long term Oral	3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	21,2 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	5,22 mg/m³	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	6 mg/kg bw/day	Workers	Systemic
cineole	DNEL	Long term Dermal	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	600 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	7,05 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1,74 mg/m³	General population	Systemic
(R)-p-mentha-1,8-diene	DNEL	Long term Inhalation	16,6 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	9,5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	4,8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	4,8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	66,7 mg/m ³	Workers	Systemic
pin-2(3)-ene	DNEL	Long term Dermal	0,225 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0,225 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	3,8 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	0,674 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0,542 mg/kg bw/day	Workers	Systemic
camphene	DNEL	Long term	110,19	Workers	Systemic

		Inhalation	mg/m³		
	DNEL	Short term Inhalation	110,19 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	54,3 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	54,3 mg/m³	General population	Systemic
	DNEL	Short term Dermal	1,25 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	0,625 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0,625 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0,1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0,1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0,21 mg/kg bw/day	Workers	Systemic
(E)-anethole	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	1,5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	1,5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2,61 mg/m ³	General population	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: It is recommended to wear a hooded visor or protective visor combined with airtight goggles (ref. Standard EN 166).

Skin protection Hand protection

: Protect hands with category III work gloves (ref. Standard EN 374). For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation. In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be

Other skin protection

- approved by a specialist before handling this product.
- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. In case of exceeding the threshold value (e.g. TLV-TWA) of the substance or of one or more of the substances present in the product, it is recommended to wear a mask with type AX filter whose limit of use will be defined by the manufacturer (ref. . standard EN 14387). If there are gases or vapors of a different nature and / or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided. The use of respiratory protection means is necessary in case the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into consideration. The protection offered by the masks is however limited. In the event that the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an open-circuit compressed air breathing apparatus (ref. Standard EN 137) or a self-contained breathing apparatus. outdoor air (ref. EN 138 standard). For the correct choice of the respiratory protection device, refer to the EN 529 standard.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state
Color
Brown.

Odor
Aromatic.
Odor threshold
Melting point/freezing point
Initial boiling point and boiling

: liquid [liquid]
Brown.
Aromatic.
Not available.
Not available.
> 100 °C (> 212 °F)

range

Flammability : Not available.

Lower and upper explosion limit : **Lower:** Not available.

Upper: Not available.

Flash point : $66 \,^{\circ}\text{C} \, (151 \,^{\circ}\text{F})$

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

pH : Product is non-polar/aprotic.

Viscosity : Dynamic : Not available.

Kinematic: Not available.

Solubility in water : insoluble

Partition coefficient: n-

octanol/water

Not applicable.

Vapor pressure :

Relative density: Not available.Vapor density: Not applicable.Explosive properties: Not available.Oxidizing properties: Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions

will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition : Under normal conditions of storage and use, hazardous

products decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

reactions

Product/ingredient name	Result	Species	Dose	Exposure
cyclohexanol				
	LD50 Oral	Rat	1.400 mg/kg	-
rosin				
	LD50 Oral	Rat	7.600 mg/kg	-
turpentine, oil				

	LD50 Oral	Rat	3.956 mg/kg	-
	LC50 Inhalation	Rat	19,9 mg/l	1 h
	Vapor			
	LC50 Inhalation	Rat	13,7 mg/l	4 h
	Vapor			
linalool				
	LD50 Oral	Rat	2.790 mg/kg	-
	LD50 Dermal	Rabbit	5.610 mg/kg	=
	LD50 Dermal	Rat	5.610 mg/kg	-
4-methylpentan-2-one				
	LD50 Oral	Rat	2.080 mg/kg	-
eugenol				
	LD50 Oral	Rat	1.930 mg/kg	-
cineole	•			
	LD50 Oral	Rat	2.480 mg/kg	-
(R)-p-mentha-1,8-diene				
	LD50 Oral	Rat	4.400 mg/kg	-
	LD50 Dermal	Rabbit	5.000 mg/kg	-
pin-2(3)-ene				
	LD50 Oral	Rat	3.700 mg/kg	-
	LD50 Dermal	Rabbit	5.000 mg/kg	-
camphene				
	LD50 Oral	Rat	5.000 mg/kg	-
	LC50 Inhalation	Rat	17,1 mg/l	1 h
	Vapor		_	
	LC50 Inhalation	Rat	17,1 mg/l	4 h
	Vapor			
(E)-anethole				
	LD50 Oral	Rat	2.090 mg/kg	-
pin-2(10)-ene				
	LD50 Oral	Rat	4.700 mg/kg	-
	LD50 Dermal	Rabbit	5.000 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
HTL000001-H002	5390,2 mg/kg	51957,9 mg/kg	N/A	50,6 mg/l	N/A
cyclohexanol	1400 mg/kg	N/A	N/A	11 mg/l	N/A
rosin	7600 mg/kg	N/A	N/A	N/A	N/A
turpentine, oil	500 mg/kg	1100 mg/kg	N/A	13,7 mg/l	N/A
linalool	2790 mg/kg	5610 mg/kg	N/A	N/A	N/A
4-methylpentan-2-one	500 mg/kg	N/A	N/A	N/A	N/A
eugenol	1930 mg/kg	N/A	N/A	N/A	N/A
cineole	2480 mg/kg	N/A	N/A	N/A	N/A
(R)-p-mentha-1,8-diene	4400 mg/kg	5000 mg/kg	N/A	N/A	N/A
pin-2(3)-ene	3700 mg/kg	5000 mg/kg	N/A	N/A	N/A

camphene	5000 mg/kg	N/A	N/A	N/A	N/A
(E)-anethole	2090 mg/kg	N/A	N/A	N/A	N/A
pin-2(10)-ene	4700 mg/kg	5000 mg/kg	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
cyclohexanol	Skin -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Rabbit	-	24 hrs	-
	irritant				
	Eyes -	Rabbit	-	24 hrs	-
	Moderate				
	irritant				
	Eyes - Mild	Rabbit	-	24 hrs	-
	irritant				
	Eyes -	Rabbit	-		-
	Moderate				
	irritant				
turpentine, oil	Skin - Severe	Rabbit	-		-
•	irritant				
	Skin - Severe	Human	-		-
	irritant				
linalool	Eyes -	Rabbit	_	1 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Man	_	48 hrs	_
	irritant			1.5	
	Skin - Mild	Rabbit	_	24 hrs	_
	irritant				
	Skin - Severe	Rabbit	_	24 hrs	_
	irritant	11110011		25	
	Eyes -	Rabbit	_		_
	Moderate	1140011			
	irritant				
	Skin -	Guinea pig	-	24 hrs	_
	Moderate	oumen pig		25	
	irritant				
	Skin - Mild	Human	_	72 hrs	_
	irritant	Tumum		, 2 ms	
4-methylpentan-2-one	Eyes -	Rabbit	_	24 hrs	_
i memyipeman 2 one	Moderate	racon		2 . 1115	
	irritant				
	Skin - Mild	Rabbit	_	24 hrs	_
	irritant	Rubbit		2.1113	
	Eyes -	Rabbit	_		_
	Severe	Rubbit			
	irritant				
eugenol	Skin -	Man	_	48 hrs	_
Cagonor	Moderate	141011		70 1113	
	irritant				
	Skin - Severe	Rabbit	-	24 hrs	_
	irritant	Kabbit	1 -	24 III S	-
	Skin - Mild	Pig	-	48 hrs	
Version: 4.0 Da	te of issue/Date of rev			ate of previous issue:	18.05.2023

	irritant				
	Skin - Moderate irritant	Guinea pig	-	24 hrs	-
	Skin - Mild irritant	Human	-	48 hrs	-
(R)-p-mentha-1,8-diene	Skin - Mild irritant	Rabbit	-	24 hrs	-
pin-2(3)-ene	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Skin - Severe irritant	Man	-		-
pin-2(10)-ene	Skin - Moderate irritant	Rabbit	-	24 hrs	-

Conclusion/Summary

Skin: Not available.Eyes: Not available.Respiratory: Not available.

Sensitization

Conclusion/Summary

Skin: Not available.Respiratory: Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
cyclohexanol	Category 3	-	Respiratory tract irritation
dodecane-1-thiol	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bornan-2-one	Category 1	-	-

Aspiration hazard

Product/ingredient name Result

turpentine, oil	ASPIRATION HAZARD - Category 1
(R)-p-mentha-1,8-diene	ASPIRATION HAZARD - Category 1
pin-2(3)-ene	ASPIRATION HAZARD - Category 1
pin-2(10)-ene	ASPIRATION HAZARD - Category 1

Information on the likely routes

of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eve contact: Adverse symptoms may include the following: pain, watering,

redness

Inhalation : Adverse symptoms may include the following: respiratory tract

irritation, coughing, wheezing and breathing difficulties, asthma, reduced fetal weight, increase in fetal deaths, skeletal malformations

Skin contact : Adverse symptoms may include the following: pain or irritation,

redness, blistering may occur, reduced fetal weight, increase in fetal

deaths, skeletal malformations

Ingestion : Adverse symptoms may include the following: stomach pains,

reduced fetal weight, increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Not available.

General : Causes damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: May damage fertility or the unborn child.

11.2. Information on other hazards

11.2.1 Endocrine disrupting properties : Not available. **11.2.2 Other information** : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
cyclohexanol			
	Acute LC50 704 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
linalool			
	Acute LC50 28,8 mg/l Fresh	Fish - Oncorhynchus mykiss	96 h
	water		
	Acute EC50 36,7 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
4-methylpentan-2-one			
	Acute LC50 505 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Chronic NOEC 168 mg/l Fresh	Fish - Pimephales promelas	33 d
	water		
	Chronic NOEC 78 mg/l Fresh	Daphnia - Daphnia magna	21 d
	water		
eugenol			
	Acute LC50 24 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
cineole			
	Acute LC50 102 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
(R)-p-mentha-1,8-diene	•	•	•
	Acute EC50 0,688 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute EC50 0,421 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
pin-2(3)-ene	•	•	•
	Acute LC50 5,28 mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water	1	
	Acute LC50 41 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
camphene	•	•	•
•	Acute LC50 1,17 mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water	•	
	Acute LC50 22 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute EC50 214 mg/l Marine	Algae - Skeletonema	96 h
	water	costatum	
(E)-anethole			
	Acute EC50 4,81 mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute EC50 4,25 mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute IC50 9,313 mg/l Fresh	Algae - Pseudokirchneriella	96 h
	water	subcapitata	
pin-2(10)-ene	•		•
	Chronic NOEC 0,058 mg/l	Fish - Oncorhynchus mykiss	60 d
	Fresh water		

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
cyclohexanol	1,21,25	-	low
bornan-2-one	2,38	-	low
rosin	1,9 - 7,7	-	high
dodecane-1-thiol	6,5	-	high
linalool	2,84	-	low
4-methylpentan-2-one	1,9	-	low
eugenol	2,27	-	low
cineole	2,74	-	low
(R)-p-mentha-1,8-diene	4,57	-	high
pin-2(3)-ene	4,487	-	high
camphene	-	954,99	high
pin-2(10)-ene	4,425	-	high

12.4 Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties : Not available.

12.7 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a

hazardous waste.

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging		European waste catalogue (EWC)
	15 01 10*	packaging containing residues of or contaminated by
		hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (rosin, turpentine, oil)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (rosin, turpentine, oil)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (rosin, turpentine, oil)
14.3 Transport hazard class(es)	9	9	
14.4 Packing group	Ш	III	III
14.5. Environmental hazards	Yes.	Yes.	Yes.

Additional information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Tunnel code (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IATA	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Restricted to professional users.

Other EU regulations

Industrial emissions (integrated

Listed

pollution prevention and control) - Air

Industrial emissions (integrated

Not listed

pollution prevention and control) - Water

Ozone depleting substances (1005/2009/EU)

None of the components are listed.

Prior Informed Consent (PIC) (649/2012/EU)

None of the components are listed.

Persistent Organic Pollutants

None of the components are listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category	
E1	

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Chemical Weapons Convention List Schedule I Chemicals

None of the components are listed.

Chemical Weapons Convention List Schedule II Chemicals

None of the components are listed.

Chemical Weapons Convention List Schedule III Chemicals

None of the components are listed.

Montreal Protocol

None of the components are listed.

Stockholm Convention on Persistent Organic Pollutants

Annex A - Elimination - Production

None of the components are listed.

Annex A - Elimination - Use

None of the components are listed.

Annex B - Restriction - Production

None of the components are listed.

Annex B - Restriction - Use

None of the components are listed.

Annex C - Unintentional - Production

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Rotterdam Convention on Prior Informed Consent (PIC) - Industrial

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) - Pesticide

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) -Severely hazardous pesticide

None of the components are listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Heavy metals - Annex 1

None of the components are listed.

POPs - Annex 1 - Production

None of the components are listed.

POPs - Annex 1 - Use

None of the components are listed.

POPs - Annex 2

None of the components are listed.

POPs - Annex 3

None of the components are listed.

Inventory list

Australia : Not determined.
Canada : Not determined.
China : Not determined.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand Not determined. **Philippines** Not determined. Republic of Korea Not determined. **Taiwan** Not determined. Thailand Not determined. Not determined. **Turkey United States** Not determined. : Viet Nam Not determined.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety

Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360	Calculation method
STOT SE 3, H335 (Respiratory tract irritation)	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H228	Flammable solid.
H290	May be corrosive to metals.

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 2	FLAMMABLE SOLIDS - Category 2
Met. Corr. 1	CORROSIVE TO METALS - Category 1
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Resp. Sens. 1	RESPIRATORY SENSITIZATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) -
	Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 3

Date of printing: 17.07.2023Date of issue/ Date of revision: 13.06.2023Date of previous issue: 18.05.2023Version: 4.0

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with

caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Notwithstanding the above, the provisions of this clause shall not apply in the event of supplier wilful misconduct (dolo), in which case the provisions of current legislation shall apply.